## STATEMENT OF WORK NAS Miramar/Navy Consolidated Brig

NCBM Miramar currently has 4 washers that are out of commission, 4 washers that are degraded, 4 dryers that are out of commission, and 3 dryers that are degraded. We need have at least 8 washers and 8 dryers to do all the laundry for our facility and all the commands that use our facility services. We currently have 3 good dryers and 1 good washer that work properly. We need a service and maintenance contract to fix and maintain routine service to the laundry equipment to prolong the life of all laundry equipment that includes 9 washer-extractors, 9 dryers, 2 ironers, 2 lint collectors and 1 press. We also have 2 new washers and 1 new dryer that have been not completely installed.

Additionally, the Contractor will provide onsite emergency repair service for the equipment listed within this contract. Response time shall be 48 hours or less from the time the call is received, Monday through Friday. All repairs will be performed and completed to manufacturer specifications by factory trained technicians.

- 1. Description of requirement for Washer-Extractors 1 thru 9
  - A. Initial visit checks and inspections to include;
    - 1. CHANGE BEARING HOUSING OIL- SAE 50 WT NON-DETERGENT
    - 2. GREASE MAIN BEARINGS
    - 3. GREASE MAJN BEARING SEALS
    - 4. CHECK LEAK-OFF PASSAGE FOR WATER
    - 5. CHANGE OIL IN GEAR BOX AND CHECK FOR OIL SEAL LEAKS
    - 6. CLEAN WATER INLET LINE STRAINER SCREENS
    - 7. REPLACE DOOR GASKET AND BUMPER
    - 8. CHECK V -BELT TIGHTNESS AND INSPECT FOR CRACKS
    - 9. CLEAN LINT OUT OF MOTORS
    - 10. CHECK TIGHTNESS OF BEARING HOUSING BOLTS/SUPPORT PLATES
    - 11. CHECK CENTRIFUGAL SWITCH ASSEMBLY OPERATION
    - 12. CHECK FILL HOSE AND DUMP VALVE TUBE HARDNESS
    - 13. CHECK DUMP VALVE MECHANISM
    - 14. CHECK FOR AIR LEAKS
    - 15 CHECK DRIVE CLUTCHES FOR WEAR
    - 16. CHECK TIMING ON BALANCE SYSTEM (BWE ONLY)
    - 17. CHECK, CLEAN, AND ADJUST BALANCE NOZZLES (BWE ONLY)
    - 18. CHECK AND FILL BALANCE SENSING UNIT- 50 WT, (BWE ONLY)
    - 19. CHECK TIMING BELTS AND TIGHTEN AS NEEDED (BWE ONLY)
    - 20. CHECK FULL LOAD AMPS ON ALL DRIVE MOTORS AND NOTE
    - 21. CHECK ELECTRONIC COMPONENTS- CLEAN AS NEEDED
    - 22. CHECK AND TIGHTEN FOUNDATION BOLTS
    - 23. CHECK AND CLEAN WATER LEVEL CONTROLS
    - 24. CHECK ALL WATER AND PNEUMATIC VALVES
    - 25. CHECK DOOR ASSEMBLIES FOR WEAR AND SMOOTH OPERATION
    - 26. CHECK AND ADJUST SELF-BALANCING SYSTEMS (BWE ONLY)
    - 27 PERFORM SAFETY AND OPERATION CHECK

- B. 12 months scheduled preventive maintenance provided in bimonthly visits to include;
  - 1. GREASE MAJN BEARINGS
  - 2. GREASE MAIN BEARING SEALS
  - 2. CHECK GEAR REDUCER OIL LEVEL- TOP-OFF AS NEEDED
  - 4. CHECK FOR OIL AND GREASE LEAKS
  - 5. CHECK BEARING HOUSING SEAL BLEED OFF FOR WATER
  - 6. OIL DOOR LOCK CYLINDER PLUNGER OR MECHANLSM
  - 7. CHECK V-BELTTIGHTNESS AND IN SPECT FOR CRACKS
  - 8. CLEAN ALL LINT OUT OF MIL TROLAND MOTORS
  - 9. CHECK FOR AIR LEAKS
  - 10. CHECK GENERAL OPERATION OF ALL ELECTRICAL COMPONENTS
  - 11. CHECK DRIVE SYSTEM COMPONENTS
  - 12. CHECK DRAIN MECHANISM OPERATION
  - 13. PERFORM SAFETY AND OPERATIONAL CHECK
- 2. Description of requirement for dryers 1 thru 10
  - A. Initial visit checks and inspections to include;
    - 1. CLEAN LINT FROM BURNERS, LINT COMPARTMENT, MOTORS, & CONTROLS
    - 2. INSTALL NEW V-BELTS AND ADJUST
    - 3. CHANGE GEAR REDUCER OIL -90 WT NON-DETERGENT DIFF LUBES
    - 4. CHECK AND LUBRICATE CHAINS, SPROCKETS, & BEARINGS
    - 5. CHECK ALL SPROCKETS AND GEARS
    - 6. CHECK CYCLINDER ALIGNMENT
    - 7. CHECK LINT SCREEN CONDITION
    - 8. CHECK IGNITION CONTROL OPERATION
    - 9. CHECK THERMOSTAT OR THERMODISC OPERATION
    - 10. CHECK ALL TIMERS
    - 11. CHECK AIR FLOW SWITCH AND DOOR SWITCH OPERATION
    - 12. CHECK GAS/AIR COMBUSTION RATIO
    - 13. CHECK EXHAUST AIR FLOW
    - 14. CLEAN LINT FROM CLEAN OUTS ON EXHAUST DUCT
    - 15. CHECK FULL LOAD AMPS ON MOTORS -LIST READINGS
    - 16. CHECK AND CLEAN COMBUSTION AIR VENTS (MAKE-UP AIR)
    - 17. CHECK DOOR AND GLASS GASKETS
  - B. 12 months scheduled preventive maintenance provided in bimonthly visits to include;
    - 1. CLEAN LINT FROM BURNERS, LINT COMPARTMENT, MOTORS, & CONTROLS
    - 2. CHECK AND TOP OFF GEAR BOX OIL LEVEL
    - 3. CHECK AND LUBRICATE CHAINS, SPROCKETS, & BEARINGS
    - 4. CHECK V-BELTS FOR TIGHTNESS AND WEAR
    - 5. CHECK THERMOSTAT OR THERMODISC OPERATION

- 6. CHECK ELECTRICAL COMPONENTS FOR WEAR
- 7. CHECK AIR FLOW SWITCH AND DOOR SWITCH OPERATION
- 8. CHECK DOOR AND GLASS GASKETS
- 9. GENERAL OPERATION OF DRYERS
- 10. CHECK CYLINDER ALIGNMENT ADJUST AS NEEDED
- 3. Description of requirement for (2) Ironers and (1) Press:
  - A. 12 months scheduled preventive maintenance provided in bimonthly visits to include;
    - 1. CHECK OIL LEVELS
    - 2. LUBRICATE LINKAGE AS NEEDED
    - 3. CLEAN AIR STRAINER, STEAM STRAINER AND AIR FILTER
    - 4. CHECK ALL STEAM & AIR CONNECTIONS FOR LEAKS
    - 5. CHECK GENERAL CONDITION OF FLEXIBLE STEAM HOSES
    - 6. CHECK VOLTAGE AND CURRENT
    - 7. REMOVE TOP COVER, REAR PANEL, FRONT PANE, BLOWER, BELT GUARDS AND CLEAN THOROUGHLY WITH VACUUM OR AIR HOSE
    - 8. CHECK FOR LOOSE BOLTS, SCREWS FITTINGS AND LEAKAGE OF OIL
    - 9. REMOVE ANY DIRT AND LINT
    - CHECK RIBBONS AND BELTS FOR FREAYING AND DAMAGED LACING
    - 11. CHECK TENSION ON DRIVE CHAINS AND BELTS
    - 12. CHECK CONDITION OF PADDING AND COVERINGS
    - 13. CLEAN & CHECK ALL VALVES & REGULATORS FOR DIRT AND PROPER OPERATION
    - 14. LUBRICATE PIVOT POINTS DAMPER SHAFT, VALVE PINS, VALVE LINKAGE AND SPRING ROD GUIDES
    - 15. CHECK WIRING AND ELCTRICAL CONNECTIONS
    - 16. INSPECT AIR LINE FILTER PARTS
    - 17. DRAIN AND CLEAN BOWL OF AIR CLEANER OF WATER AND DIRT
- 4. Description of requirement for (2) Lint Filters:
  - A. Initial visit checks and inspections to include;
    - 1. THOROUGH INSPECTION OF EQUIPMENT
    - 2. BLOW DOWN OR VACUUM EXCESSIVE LINT BUILDUP IN FILTER
    - 3. REMOVE SCREEN AND CLEAN, CHECK FOR HOLES AND/OR WEAR PRIOR TO REINST ALLA TION
    - 4. CHECK TOP SWIVEL ROTOR AND BOTTOM BUSHINGS FOR EXCESSIVE WEAR, LINT, OR OTHER DEBRIS. CLEAN AS REQUIRED.
    - 5. CHECK TO MAKE SURE ALL HOLES ARE OPEN IN BLOW DOWN MECHANISM AND THAT MECHANISM TURNS FREELY
    - 6. TEST EMERGENCY FIRE CONTROL AND OVERPRESSURE ALARM (IF APPLICABLE)
    - 7. CHECK INSPECTION DOOR GASKET FOR LEAKS
    - 8. CHECK LINT COLLECTOR BAG FOR SNUG FIT, CHECK FOR TEARS OR EXCESSIVE WEAR

- B. 12 months scheduled preventive maintenance provided in bimonthly visits to include;
  - 1. CLEAN RESIDUE, TRASH, AND STRING FROM LINT COLLECTOR
  - 2. OPEN INSPECTION DOOR AND CHECK BLOW DOWN MECHANISM
  - 3. INSPECT SCREEN CONDITION
  - 4. TEST EMERGENCY FIRE CONTROL AND OVERPRESSURE ALARM (IF APPLICABLE)
  - 5. CHECK INSPECTION DOOR GASKET FOR LEAKS
  - 6. CHECK LINT COLLECTOR BAG FOR SNUG FIT, CHECK FOR TEARS OR EXCESSIVE WEAR
- 5. Delivery/Performance Schedule:

Base Period October 1, 2013 – September 30, 2014 Option Period One October 1, 2014 – September 30, 2015 Option Period Two October 1, 2015 – September 30, 2016

6. List of all Dryers, Washers, Ironers, and Presses including make, model, serial numbers and status provided.